

Die Casting Plunger Pressing Velocity and Analysis of Its Influence on a Permanent Deformation Value of a Casting Made from an ENAC 47100 Alloy

Assoc. Prof. Paško Ján, MSc., PhD., Department of Technical Devices Design, Technical University of Košice, Faculty of Manufacturing Technologies with seat in Prešov, Slovak Republic

A die casting plunger velocity inside a filling chamber of a pressure die casting machine is one of the most significant factors of a pressure die casting. This velocity determines the regime of a die cavity filling, thus influencing both inner and surface quality of castings. A selection of a correct velocity of a die cavity filling depends on such factors as an alloy type, a casting complexity, a ratio of a slot area to a casting area, etc. A static pressure test can be used to determine a permanent deformation value by which a casting quality can be considered.

Keywords: die casting plunger pressing velocity, ENAC 47100 alloy, permanent deformation, homogeneity of a casting

References

- [1] GME 60 007, Aluminiumteile fur Treibwerkklagerung und Aluminiuminnenkerne von Dämpfungsblocken, Conti Tech Vegum VC s.r.o. Úsek riadenia kvality, 25.5.2001.
- [2] GME 60 156, Test Method for Determining the Compression Properties of Centre Tubes, Vauxhallm Morors LTD, 11.1.2001.
- [3] MALIK, J.: Technológia tlakového liatia hliníka, Habilitačná práca, TU-HF Košice, 2008.
- [4] RAGAN, E a kol.: Liatie kovov pod tlakom, FVT Prešov, 2007.
- [5] STN EN 1706, Hliník a zliatiny hliníka, Odliatky, Chemické zloženie a mechanické vlastnosti.
- [6] NOVÁ, I., SOLFRONK, P., NOVÁKOVÁ, I. Vliv tlaku na strukturu slitiny hliníku AlCu4MgTi. In *Strojírenská technologie*, 2010, roč. XV, č. 3., Str. 11 – 17, ISSN 1211-4162.
- [7] MICHNA, Š. Legování hliníkových slitin pomocí chromových legovacích tablet. In *Strojírenská technologie*, 2010, roč. XV, č.1., Str. 22 – 26, ISSN 1211-4162.

Reviews:

Prof. Iva Nová, MSc., Ph.D.
Assoc. Prof. Dana Bolibruchová, MSc., PhD.