## **Cutting Tool Performance in End Milling of Glass Fiber-Reinforced Polymer Composites**

Ondřej Bílek, Milan Žaludek, Jiří Čop

Department of Production Engineering, Faculty of Technology, Tomas Bata University in Zlin, Vavreckova 275, 760 01 Zlin, Czech Republic. E-mail: bilek@ft.utb.cz, zaludek@ft.utb.cz, cop@ft.utb.cz

The article deals with the machining of glass fiber-reinforced thermoset composite. Emphasis is placed on the selection of cutting tools for end milling. Experiment involved slot milling by special tools for composite machining with different geometries and surface coating. Further, the quality of the machined surface, cutting performance, dimensional accuracy, delamination factor and tool wear were evaluated. The results were compared with the end milling of carbon fiber-reinforced polymer composites.

Keywords: End Milling, GFRP, CFRP, Composites, Cutting Tools.

## Acknowledgments

This study was supported by the internal grant of TBU in Zlín No. IGA/FT/2016/002 funded from the resources of specific university research.

## References

- AZMI, A. I., LIN, R.J.T., BHATTACHARYYA, D. (2012). Experimental Study of Machinability of GFRP Composites by End Milling. In: *Materials and Manufacturing Processes*, Vol. 27, pp.1045–1050. Taylor & Francis, UK.
- [2] AZMI, A.I. ET AL. (2011). Parametric Study of End Milling Glass Fibre Reinforced Composites. In: *INTERNATIONAL CONFERENCE ON ADVANCES IN MATERIALS AND PROCESSING TECHNOLOGIES* (AMPT2010), pp. 1083–1088. American Institute of Physics, US.
- [3] BEŇO, J., MIKÓ, B., MAŇKOVÁ, I., VRABEL, M. (2013). Influence of Tool Path Orientation on the Surface Roughness when End Ball Milling Rounded Surfaces. In: *Key Engineering Materials*, Vol. 581, pp. 329–334. TTP. Switzerland.
- [4] DAVIM, J.P., REIS, P. (2005). Damage and dimensional precision on milling carbon fiber-reinforced plastics using design experiments. In: *Journal of Materials Processing Technology*, Vol. 160, pp.160–167.
- [5] EL-HOFY, M.H. ET AL. (2011). Factors affecting workpiece surface integrity in slotting of CFRP. In: *Procedia Engineering*, Vol. 19, pp. 94–99.
- [6] GOTTFRIED W. E. (2009). *Polymer composite materials* (Polymerní kompozitní materiály). Scientia. Czech Republic.
- [7] HINTZE WOLFGANG, W., HARTMANN, D., SCHÜTTE, C. (2011). Occurrence and propagation of delamination during the machining of carbon fibre reinforced plastics (CFRPs) An experimental study. In: *Composites Science and Technology*, Vol. 71, No. 15, pp.1719–1726.
- [8] HOLESOVSKY, F., NOVAK, M., LATTNER, M., VYSLOUZIL, T. (2013). Machining and its Influence to Surface Quality of Machine Parts. In: *Key Engineering Materials*, Vol. 581, pp.354–359. TTP. Switzerland.
- [9] HUSSAIN, S.A., PANDURANGADU, V. & KUMAR, K.P. (2011). Machinability of glass fiber reinforced plastic (GFRP) composite materials. In: *International Journal of Engineering, Science and Technology*, Vol. 3, No. 4, pp.103–118.
- [10] JERSÁK, J., VRKOSLAVOVÁ, L. (2013). The influence of process fluids on the properties of the surface layer of machined components. In. *Manufacturing Technology*, Vol. 13, No. 4, pp. 466–473. UJEP, Czech Republic.
- [11] JÓZWIK, J., KURIC, I., SÁGA, M., LONKWIC, P. (2014). Diagnostics of CNC machine tools in manufacturing process with laser interferometer technology. In: *Manufacturing Technology*, Vol. 14, No. 1, UJEP, Czech Republic
- [12]KASINA, M., VASILKO, K. (2012). Experimental verification of the relation between the surface roughness and the type of used tool coating. In: *Manufacturing Technology*, Vol. 12, pp. 27–30. UJEP, Czech Republic
- [13] KOCMAN, K. (2011). Application of magnetic correlation analysis on the choice and correction of cutting parameters for automated manufacturing systems. In: *Manufacturing Technology*, Vol. 11, pp. 28–32. UJEP, Czech Republic

- [14] LEGUTKO, S., KROLCZYK, G., KROLCZYK, J. (2014). Quality evaluation of surface layer in highly accurate manufacturing. In: *Manufacturing Technology*, Vol. 14, No. 1, pp.50–56. UJEP, Czech Republic
- [15] MIROSLAV, M., PETR, V. (2012). Abrasive wear effect on Polyethylene, Polyamide 6 and polymeric particle composites. In: *Manufacturing Technology*, Vol. 12, pp. 55–59. UJEP, Czech Republic
- [16] PECAT, O., RENTSCH, R., BRINKSMEIER, E. (2012). Influence of milling process parameters on the surface integrity of CFRP. In: *Procedia CIRP*, Vol. 1, pp. 466–470.
- [17] TETI, R. (2002). Machining of Composite Materials. In: CIRP Annals Manufacturing Technology, Vol. 51, pp.611–634.
- [18] UHLMANN, E. ET AL. (2014). Machining of Carbon Fibre Reinforced Plastics. In: *Procedia CIRP*, Vol. 24, pp. 19–24.
- [19] VARGA, G., KUNDRÁK, J. (2013). Effect of Environmentally Conscious Machining on Machined Surface Quality. In: *Applied Mechanics and Materials*, Vol. 309, pp. 35–42.
- [20] WANG, Y.G. et al. (2011). Cutting Performance of Carbon Fiber Reinforced Plastics Using PCD Tool. In: *Advanced Materials Research*. Vol. 215, pp. 14–18. TTP. Switzerland.

Paper number: M20162

Copyright @ 2016. Published by Manufacturing Technology. All rights reserved.